

Technical data sheet

BauderPVC NA

PVC seam activator



24/03/2026

| | |
|---------------------------|---|
| Application fields | Should be used for preparing seams of aged or heavily soiled Thermofol PVC. Membrane for hot air welding. |
| Colour | Clear |
| Article number | 6051 0025 |
| Website link | https://www.bauder.co.uk/products/pvc-na-seam-activator |



| Characteristic | Unit | Value |
|----------------------------------|------------------|--|
| Chemical base | - | Solvent mixture on acetone basis |
| Product storage | - | store closed and cool |
| Flash point | °C | 99 |
| Density | g/m ³ | 1.095 |
| Viscosity | - | thin liquid |
| Consumption | - | 30-60 g/lm seam depending on pollution |
| Reaction to fire | - | No hazardous goods |
| Health risk | - | No hazardous goods |
| Package size | - | 2,5 l |
| External fire performance | - | not applicable |

Normative references

For undated references, the latest edition of the referenced document (including any amendments) applies.

Handling/PPE

All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using/handling the product, installers should be provided with, and wear, suitable personal protective equipment.

Further information/documents

Current documents such as DoP's (where relevant), brochures, installation guides, etc. can be found by visiting www.bauder.co.uk

Safety Data Sheet

Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as a substance/mixture; therefore, this product does have a requirement for a Safety Data Sheet.