

# Bauder LiquiTOP General Purpose Primer

## safety data sheet

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Revision date: 19.09.2025

Supersedes : March 2022

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Trade name : Bauder LiquiTOP General Purpose Primer  
Article Number : GB81008110

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Adhesive

Recommended restrictions on use : For industrial use only.  
For professional users only.  
For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Supplier : Bauder Ltd  
70 Landseer Road  
Ipswich  
Suffolk  
IP3 0DH  
Tel: +44 (0) 1473 257671  
Email: info@bauder.co.uk

#### 1.4 Emergency telephone number

NPIS (National Poisons Information Service): 0344 892 0111 (for medical professionals only).

For medical advice, members of the public should contact NHS 111

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture


Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

|                               |                                     |
|-------------------------------|-------------------------------------|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapour.  |
| Acute toxicity, Category 4    | H332: Harmful if inhaled.           |
| Acute toxicity, Category 4    | H312: Harmful in contact with skin. |
| Skin irritation, Category 2   | H315: Causes skin irritation.       |

|  |  |
|--|--|
| Eye irritation, Category 2   | H319: Causes serious eye irritation.   |
| Respiratory sensitisation, Category 1  | H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Skin sensitisation, Category 1   | H317: May cause an allergic skin reaction.                                       |
| Carcinogenicity, Category 2  | H351: Suspected of causing cancer.   |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation.  |
| Specific target organ toxicity - repeated exposure, Category 2                   | H373: May cause damage to organs through prolonged or repeated exposure.         |

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

|                          |   |  |
|--------------------------|---|--|
| Hazard pictograms        | : |   |
| Signal word              | : | Danger   |
| Hazard statements        | : | H226 Flammable liquid and vapour.<br>H312 + H332 Harmful in contact with skin or if inhaled.<br>H315 Causes skin irritation.<br>H317 May cause an allergic skin reaction.<br>H319 Causes serious eye irritation.<br>H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.<br>H335 May cause respiratory irritation.<br>H351 Suspected of causing cancer.<br>H373 May cause damage to organs through prolonged or repeated exposure.  |
| Precautionary statements | : | <b>Prevention:</b><br>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P260 Do not breathe mist or vapours.<br>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.<br><b>Response:</b><br>P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.<br>P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.<br>P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |

### Hazardous components which must be listed on the label:

xylenes

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate

### Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

No information available

### 3.2 Mixtures

#### Components

| Chemical name  | CAS-No. EC-No. Index-No. Registration number   | Classification  | Concentration (% w/w) |
|--|--|---|-----------------------|
| xylenes  | 1330-20-7<br>215-535-7<br>601-022-00-9<br>01-2119488216-32-0000, 01-2119486136-34-0000 | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315   | >= 50 - < 70          |
| Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate | 26447-40-5<br>905-806-4  | Acute Tox. 4; H332<br>Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>Carc. 2; H351 STOT SE 3; H335 (Respiratory system)<br>STOT RE 2; H373 | >= 20 - < 30          |

For explanation of abbreviations see section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

General advice : Immediately remove clothing if soiled by product. Move the victim to fresh air.  
Even minimal concentrations of isocyanate can lead to a reaction in sensitised people.  
Symptoms that may occur include the following:  
irritation of the eyes, nose, throat and lungs, possibly together with a dry throat, a feeling of chest tightness and breathing difficulties.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.  
Show this safety data sheet to the doctor in attendance.

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.  
In case of unconsciousness bring patient into stable side position for transport.
- In case of skin contact : Treat affected skin with cotton wool or cellulose.  
Wash off with plenty of water.  
Use a mild soap if available.  
If skin irritation persists, call a physician.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : If accidentally swallowed obtain immediate medical attention. Do NOT induce vomiting.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Harmful in contact with skin or if inhaled.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause respiratory irritation.  
Suspected of causing cancer.  
May cause damage to organs through prolonged or repeated exposure.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : In instances of existing sensitisation towards isocyanates, a doctor should be consulted with regards to work-related contact with other sensitising substances, or substances which irritate the airway.  
Treatment for exposure should be geared towards monitoring symptoms and the patient's clinical condition.  
It must be ensured that the patient has sufficient ventilation and oxygen supply.  
Isocyanates can cause sensitisation of the airways, or asthma-like symptoms (bronchospasms). Delayed breathing symptoms, including lung oedema, may occur.  
People who have shown signs of breathlessness after considerable exposure should remain under observation for 24-48 hours.

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Alcohol-resistant foam  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : Water with a full water jet

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : May release toxic, irritating and/or corrosive gases.  
In case of fire CO, NO<sub>x</sub>, isocyanates and traces of HCN can be formed.

## 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.  
Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Use breathing protection against the effects of fumes/dust/aerosol.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation.

## 6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.  
Prevent the material from reaching sewage system, holes and cellars.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Non-sparking tools should be used. Ensure adequate ventilation.  
Send for recovery or disposal in suitable containers.  
Dispose of contaminated material as waste according to section 13.

## 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8. For disposal considerations see section 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Advice on safe handling : Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the vapor concentration below the work-place limit, wear an adequate respiratory protective device.

Take note of emission threshold. Avoid formation of aerosol.  
 Use solvent-proof equipment.  
 Ensure that suitable extractors are available on processing machines.  
 Handle with care. Avoid inhalation and skin contact. Keep eye wash bottle available on working place.  
 Avoid release to the environment. Keep out of reach of children.

Advice on protection against fire and explosion : Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mixtures in air. Highly volatile, flammable constituents are released during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep dark, cool and dry. Store in cool place.

Further information on storage conditions : Store in a cool place. Heat will increase pressure and may lead to the container exploding. Keep containers tightly closed in a dry, cool and well-ventilated place. Prevent any seepage into the ground.

Advice on common storage : Keep away from food, drink and animal feed.

Dampness : Keep containers dry and tightly closed to avoid moisture absorption and contamination.

### 7.3 Specific end use(s)

Specific use(s) : No further relevant information available.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components  | CAS-No.   | Value type (Form of exposure) | Control parameters              | Basis   |
|---|-----------|-------------------------------|---------------------------------|---------|
| xylenes   | 1330-20-7 | TWA                           | 50 ppm<br>220 mg/m <sup>3</sup> | GB EH40 |
| Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will |           |                               |                                 |         |

|  |  |                      |            |
|--|--|----------------------|------------|
|  | lead to systemic toxicity.   |                      |            |
|  | STEL   | 100 ppm<br>441 mg/m3 | GB EH40    |
|  | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                      |            |
|  | TWA  | 50 ppm<br>221 mg/m3  | 2000/39/EC |
|  | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |                      |            |
|  | STEL   | 100 ppm<br>442 mg/m3 | 2000/39/EC |
|  | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |                      |            |

**Derived No Effect Level (DNEL):**

| Substance name | End Use | Exposure routes | Potential health effects | Value     |
|----------------|---------|-----------------|--------------------------|-----------|
| xylenes        | Workers | Inhalation      | Local, long-term         | 221 mg/m3 |
|                | Workers | Inhalation      | Systemic, short-term     | 442 mg/m3 |
|                | Workers | Inhalation      | Systemic, long-term      | 221 mg/m3 |
|                | Workers | Dermal          | Systemic, long-term      | 212 mg/kg |
|                | Workers | Inhalation      | Local, short-term        | 442 mg/m3 |
|                | Workers | Eye contact     | Local effects            |           |

**Predicted No Effect Concentration (PNEC):**

| Substance name | Environmental Compartment | Value       |
|----------------|---------------------------|-------------|
| xylenes        | Soil                      | 2,31 mg/kg  |
|                | Marine sediment           | 12,46 mg/kg |
|                | Fresh water sediment      | 12,46 mg/kg |
|                | Sewage treatment plant    | 6,58 mg/l   |
|                | Fresh water               | 0,327 mg/l  |
|                | Marine water              | 0,327 mg/l  |

**8.2 Exposure controls**

**Engineering measures**

Please take care on national and local requirements.

**Personal protective equipment**

Eye protection : Tightly fitting safety goggles

Hand protection

Remarks : Direct contact with the product must be avoided by organizational measures.

The glove material has to be impermeable and resistant to the product/the substance/the preparation.  
The exact break through time can be obtained from the protective glove producer and this has to be observed.  
The gloves need to be disposed after the penetration time and

replaced by new ones.

Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

**For the permanent contact gloves made of the following materials are suitable:**

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

**As protection from splashes gloves made of the following materials are suitable:**

Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

|                          |   |  |
|--------------------------|---|--|
| Skin and body protection | : | Protective clothing<br><br>When carrying out activities where unintentional skin contact with the isocyanate-based product may occur (e.g. during maintenance work, or when opening a barrel), wear long-sleeved protective clothing and gloves.   |
| Respiratory protection   | : | Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.<br>In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus.<br>In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. |
| Filter type              | : | For short term use a combination of charcoal filter and particulate filter is recommended.   |
| Protective measures      | : | Instantly remove any soiled and impregnated garments.<br>Wash hands before breaks and immediately after handling the product.<br>Avoid contact with the eyes and skin. Store protective clothing separately.<br>Keep away from food, drink and animal feeding.   |

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information of basic physical and chemical properties

|  |   |  |
|--|---|--|
| Appearance                             | : | liquid   |
| Colour                                 | : | brown  |
| Odour                                  | : | characteristic   |
| Odour Threshold                        | : | is not determined  |
| pH                                     | : | is not determined  |
| Melting point/freezing point           | : | is not determined  |
| Boiling point/boiling range            | : | is not determined  |
| Flash point                            | : | 25 °C  |
|  |   | see user defined free text   |
| Evaporation rate                       | : | is not determined  |
| Relative vapour density                | : | is not determined  |
| Density                                | : | 1,0 g/cm <sup>3</sup>  |
| Solubility(ies)                        |   |  |
| Water solubility                       | : | partly soluble, reacts with water  |
| Partition coefficient: n-octanol/water | : | no data available  |
| Auto-ignition temperature              | : | is not determined  |
| Decomposition temperature              | : | Not applicable   |
| Viscosity                              |   |  |
| Viscosity, kinematic                   | : | 20,5 mm <sup>2</sup> /s (40 °C)  |
| Explosive properties                   | : | Product is not explosive. However, formation of explosive vapour/air mixtures is possible. |

### 9.2 Other information

No data available

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No further relevant information available.

### 10.2 Chemical stability

No decomposition if used according to the specifications.

### 10.3 Possibility of hazardous reactions

|                     |   |   |
|---------------------|---|---|
| Hazardous reactions | : | Develops readily flammable vapours/fumes.<br>Reacts with alcohols, amines, aqueous acids and alkalis. Mixture reacts with water resulting in evolution of CO <sub>2</sub> .<br>Evolution of CO <sub>2</sub> in closed containers causes overpressure and produces a risk of bursting. |
|---------------------|---|---|

### 10.4 Conditions to avoid

|                     |   |  |
|---------------------|---|--|
| Conditions to avoid | : | No further relevant information available. |
|---------------------|---|--|

### 10.5 Incompatible materials

|                    |   |  |
|--------------------|---|--|
| Materials to avoid | : | No further relevant information available. |
|--------------------|---|--|

## 10.6 Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as:

Nitrogen oxides (NO<sub>x</sub>)  
Isocyanates

Additional information: Open and release pressure carefully with pressurised containers.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information of toxicological effects

#### Acute toxicity

Harmful in contact with skin or if inhaled.

#### Product:

|                           |   |  |
|---------------------------|---|--|
| Acute inhalation toxicity | : | Acute toxicity estimate: 13,53 mg/l<br>Exposure time: 4 Hours<br>Test atmosphere: vapour<br>Method: Calculation method |
| Acute dermal toxicity     | : | Acute toxicity estimate: 1.836 mg/kg<br>Method: Calculation method   |

#### Components:

##### Xylenes

|                           |   |  |
|---------------------------|---|--|
| Acute oral toxicity       | : | LD50 Oral (Rat): 4.300 mg/kg   |
| Acute inhalation toxicity | : | LC50 (Rat): 47.635 mg/l<br>Exposure time: 4 Hours<br>Test atmosphere: vapour |

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

##### Skin sensitisation

May cause an allergic skin reaction.

##### Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Suspected of causing cancer.

### Reproductive toxicity

Based on available data, the classification criteria are not met.

### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

Based on available data, the classification criteria are not met.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

#### xylenes:

Partition coefficient: : log Pow: 2,77 - 3,15  
noctanol/water : GLP: no

### 12.4 Mobility in soil

#### Product:

Mobility : Medium: Soil  
Remarks: Do not allow product to reach ground water, water bodies or sewage system.

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

No data available

## 12.7 Other adverse effects

No data available

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

- Product : Do not dispose of with domestic refuse.  
Do not dispose of waste into sewer.  
Hand over to disposers of hazardous waste.  
The generation of waste should be avoided or minimized wherever possible.  
Incinerate under controlled conditions in accordance with all local and national laws and regulations.  
Disposal must be made according to official regulations.
- Contaminated packaging : Disposal must be made according to official regulations.

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number

- ADN : UN 1139  
ADR : UN 1139  
RID : UN 1139  
IMDG : UN 1139  
IATA : UN 1139  
Not permitted for transport

### 14.2 UN proper shipping name

- ADN : COATING SOLUTION  
ADR : COATING SOLUTION  
RID : COATING SOLUTION  
IMDG : COATING SOLUTION  
IATA : COATING SOLUTION  
Not permitted for transport

### 14.3 Transport hazard class(es)

- ADN : 3  
ADR : 3  
RID : 3  
IMDG : 3  
IATA (Cargo) : 3  
IATA (Passenger) : Not permitted for transport

## 14.4 Packing group

### ADN

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

### ADR

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)  
Remarks : This product is eligible to ship using the Limited Quantity exception when packed in inner packaging with a maximum content of 5 liters and outer packaging up to 30 kg

### RID

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

### IMDG

Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
IATA (Cargo) : Not permitted for transport  
IATA (Passenger) : Not permitted for transport

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the

properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environment regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

|  |   |
|--|---|
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : Conditions of restriction for the following entries should be considered:<br>Number on list 75, 3<br><br>xylenes<br>benzoyl chloride<br>Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate<br>Diphenylmethanediisocyanate, polymeric (Number on list 74)<br>xylenes |
| REACH - Candidate List of Substances of Very High Concern for Authorisation (SVHC, Article 59)   | : Not applicable  |
| Regulation (EU) No 2024/590 on substances that deplete the ozone layer   | : Not applicable  |
| Regulation (EU) 2019/1021 on persistent organic pollutants (recast)  | : Not applicable  |
| RoHS: 2011/65/EU, Restriction of Hazardous Substances  | : Not applicable  |
| Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals             | : Not applicable  |
| UK REACH List of substances subject to authorisation (Annex XIV)   | : Not applicable  |

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 59,94 %

**The components of this product are reported in the following inventories:**

REACH : On the inventory, or in compliance with the inventory

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 : May cause respiratory irritation.  
H351 : Suspected of causing cancer.  
H373 : May cause damage to organs through prolonged or repeated exposure.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Carc. : Carcinogenicity  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Resp. Sens. : Respiratory sensitisation  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration

associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Contact Point : Prepared by: Global Regulatory Department  
[EU-MSDS@hbfuller.com](mailto:EU-MSDS@hbfuller.com)

#### Classification of the mixture:

|               |      |
|---------------|------|
| Flam. Liq. 3  | H226 |
| Acute Tox. 4  | H332 |
| Acute Tox. 4  | H312 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2  | H319 |
| Resp. Sens. 1 | H334 |
| Skin Sens. 1  | H317 |
| Carc. 2       | H351 |
| STOT SE 3     | H335 |
| STOT RE 2     | H373 |

#### Classification procedure:

Based on product data or assessment

Calculation method

Calculation method

Calculation method

Calculation method

Calculation method

Calculation method

Calculation method

Calculation method

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

Bauder reserves the right to amend information and product specifications without prior notice. All reasonable care has been taken to ensure that all data is current at the time of print, however because Bauder pursues a policy of constant development we recommend ensuring that your copy of this information is current by contacting our Technical Department at [technical@bauder.co.uk](mailto:technical@bauder.co.uk)  
Recommendations for use should be verified as to the suitability and compliance with actual requirements, specifications, installation techniques and any applicable laws and regulations.