

# Technical data sheet

## BauderTHERMOFOL D 18

### PVC Detailing membrane



26/11/2025

<b>Product description</b>	Unreinforced PVC-P single ply roofing membrane	
<b>Application fields</b>	This detailing membrane should be used around penetrations and at details where movement of the structure(s) is likely.	
<b>Surface</b>	top:	light grey RAL 7035
	bottom:	black
<b>Reinforcement type and weight</b>	unreinforced	
<b>Article number</b>	6101 0050	
<b>Website link</b>	<a href="https://www.bauder.co.uk/products/bauderthermofol-d-18">https://www.bauder.co.uk/products/bauderthermofol-d-18</a>	



Characteristic	Test method	Unit	Value
Visible defects	EN 1850-2	-	no visible defects
Length	EN 1848-2	m	10 (-0/+5%)
Width	EN 1848-2	m	0,5 (-0,5/+1%)
Straightness	EN 1848-2	mm	< 30
Flatness	EN 1848-2	mm	< 10
Mass per unit area	EN 1849-2	kg/m <sup>2</sup>	2,2 (-5/+10%)
Effective thickness	EN 1849-2	mm	1,8 (-5/+10%)
Water tightness	EN 1928 - B	-	passed
Reaction to fire	EN 13501-1	-	class E
Joint peel resistance	EN 12316-2	N/50mm	≥200
Joint shear resistance	EN 12317-2	N/50mm	≥450
Tensile strength Id	EN 12311-2 B	N/mm <sup>2</sup>	≥13
Tensile strength td	EN 12311-2 B	N/mm <sup>2</sup>	≥13
Elongation Id	EN 12311-2 B	%	≥300
Elongation td	EN 12311-2 B	%	≥300
Tear resistance (length)	EN 12310-2	N	> 150
Tear resistance (transversal)	EN 12310-2	N	> 150
Dimensional stability Id	EN 1107-2	%	≤2
Flexibility at low temperature	EN 495-5	°C	≤ -30
UV exposure	EN 1297	-	passed, class 0 ( > 5000 h )
Water vapour transmission	EN 1931	-	20000 (±30%)
sd-value	EN 1931	m	36

# Technical data sheet

## BauderTHERMOFOL D 18

### PVC Detailing membrane



Characteristic	Test method	Unit	Value
External fire performance	CEN/TS 1187	-	not applicable

<b>Product surface finish</b>	BauderTHERMOFOL D has a standard thickness of 1.8mm to ensure a minimum thickness of membrane for all applications.
<b>Product storage guidance</b>	Store the materials outdoors, laid horizontal/flat and off the ground with suitable robust UV resistant, flame-retardant tarpaulin. Ensure the product(s) are clear of buildings and any other storage areas. Where there are storage containers on site, these may be suitable for storing products.
<b>Pallet size</b>	Pallet size = 60 rolls/300m <sup>2</sup> per pallet
<b>Packaging material</b>	The product will be delivered on wooden pallets with polyethylene overwrap to protect the product. Each roll has a recycled cardboard core. Recycled nylon straps contain the rolls on a pallet.
<b>Handling/PPE</b>	All persons using the product should be fully aware of the manual handling methods as roofing materials are heavy and can cause serious injury. When using/handling the product, installers should be provided with, and wear, suitable personal protective equipment.
<b>Disposal guidance</b>	Waste of the product is not a hazardous substance. Observe local regulations. European Waste Catalogue EWC number 170203 "Plastic Mirror Non hazardous"
<b>Re-use options of product</b>	Please refer to EPD stated below in Certification and environmental information.
<b>Further information/documents</b>	Current documents such as DoP's (where relevant), brochures, installation guides, etc. can be found by visiting <a href="http://www.bauder.co.uk">www.bauder.co.uk</a>
<b>Certification and environmental information</b>	<p><b>BBA Certificate No.:</b> 06/4354</p> <p><b>FM Approval:</b> Not applicable</p> <p><b>Environmental Product Declaration:</b> EPD-BAU-20130189-IBCC-DE</p> <p><b>International Standards Organisation (ISO):</b> ISO 9001:2015 Quality Management Certificate 70499/03-15_e (Germany)</p> <p>ISO 14001:2015 Environmental Management Certificate 70499/03-15_d (Germany)</p> <p>ISO 50001: 2011 Energy Management Certificate 70499/03-15_c (Germany)</p>
<b>Safety Data Sheet</b>	Safety Data Sheets are designed to provide the necessary information to recipients of substances and mixtures in the EU & UK. This product is classed as an article; therefore, this product does not have a requirement for a Safety Data Sheet.