

CONTRACTOR UPDATE

PVC Seam Activator

As a result of our continued system development, we have added to our range of accessories a new PVC Seam Activator to assist during the installation of aged or heavily soiled Thermofol PVC membrane.

Bauder PVC Seam Activator should be used for preparing the welding zones of Thermofol PVC Membranes that are not adequately clean before hot air welding. It is not suitable as a general-purpose cleaner to remove dirt or bitumen residue from Thermofol membrane; Bauder PVC Cleaner is the recommended product for those requirements.



- Apply Bauder PVC Seam Activator with a soft and clean tissue onto the welding zone.
- Clean the membrane and wipe dry with lint free tissues.
- If the membrane is particularly dirty, wipe several times with Bauder PVC Seam Activator and a new lint free tissue until the original membrane colour is restored.
- Allow the PVC Seam Activator to evaporate completely (5 minute ventilation period) before hot air welding is carried out.
- Do not use PVC Seam Activator to clean the whole membrane surface; it is only for seam preparation.

Bauder PVC Seam Activator is available from our Ipswich warehouse and is supplied in 2.5ltr containers.

Coverage rate: Approx. 60 linear metres of heavily soiled membrane welding zone per container.

Lead-time: 2-3 working days as per our latest delivery guide.

List price: £13.05 per ltr (£32.63 per container).

This product is available with immediate effect and will be added to the Thermofol Price List when it is next updated; if you require any further information relating to this product please get in touch with your local ATM or contact me directly.

Regards

Chris Lee

Single Ply Product Manager

Tel: 07590 964784

Email: c.lee@bauder.co.uk